

Turbo-2200**C-Band dual-pol. Twin Output LNBF**

turbo-2200 C-Band dual-pol. Twin Output LNBF has two C-Band single polarity signal outputs independently (one for horizontal polarity, another for vertical polarity), it is especially suitable for two polarity digital satellite receptions at the same time in CATV headend system or multi DTH users with additional multi switch device.

**Specifications**

Input Frequency Range	3.4~4.2GHz
Output Frequency Range	950~1750MHz (two ports output) one for vertical, another for horizontal
L.O. Frequency	5150MHz
L.O. Frequency stability	±0.5M
L.O. Phase Noise	-65dBc/Hz@1KHz ; -85dBc/Hz@10KHz ; -100dBc/Hz@100KHz
Noise Temperature	17~20K
Conversion Gain	65dB (type)
Gain Variation	±0.5dB/27MHz
Image Rejection	45dB (min.)
Output Power (at 1dB Compression Point)	0dBm (min.)
Crosstalk Isolation	20dB (type)
Output Spurious	-60dBm(max.)
Output VSWR	2:1
Power Supply	10.5~21V DC, 250mA
Output Impedence	75Ω two F-type Female
Operating Temperature	-30°~ 60°C
Dimensions	185mmx125mmx170mm
Weight	540g

Specifications are subject to change without notice

Team-up with PBI, Brighten Your Digital View!

WWW.PBI-CHINA.COM



北京普博信科技发展有限公司
 地址: 北京市海淀区中关村大街100号106室
 邮编: 100080
 电话: 010-82685998 010-82685971
 E-mail: mkt@pbi-china.com

Room 106, QingYuan Building, No.33 RenDa Beilu,
 Haidian District, Beijing, China, 100080
 Tel: +86-10-82685998 Fax: +86-10-82685971